





## Agenda

- Background
- Impact of Mask on Interference
- Leveraging Commercial Off-the-Shelf (COTS) Technology
- Conclusions



### 4.9 GHz Chronology

• 2000	Public Safety initiates campaign for dedicated PS broadband spectrum
• Feb 2002	FCC designates 50 MHz at 4.9 GHz for Public Safety based on mission critical need
• May 2003	FCC adopts 4.9 GHz technical and licensing rules  » Promotes Efficient Reuse and Interference Protection  » Incorporates Flexible Channel Plan for Multiple Scenarios
• July 2003	NPSTC raises concern about mask, lack of interoperability standards and loose regional planning rules
• Oct. 2003	Comments/Replies filed with FCC



**FCC** decision on NPSTC Petition

Oct. 2003 TIA initiates 4.9 GHz standards activity

TBD

<u>Position</u>	<b>NPSTC</b>	<u>Motorola</u>
<ul> <li>PS needs its own band</li> </ul>	Yes	Yes
<ul> <li>Leverage 5 GHz technology for 4.9 GHz</li> </ul>	Yes	Yes
<ul> <li>Need a 4.9 industry standard (TIA)</li> </ul>	Yes	Yes
<ul> <li>Need regional planning</li> </ul>	Yes	Yes
<ul> <li>Leverage DSRC masks</li> </ul>	Yes	Yes
<ul> <li>Tighter mask for higher power</li> </ul>	Yes	Yes
<ul> <li>Threshold for tighter mask</li> </ul>	<b>20</b> dBm	0 dBm
<ul> <li>User scenario is key deciding factor for interference</li> </ul>	Yes	Yes
<ul> <li>4.9 Scenarios are established</li> </ul>	Yes	No
<ul> <li>FCC Mask is significant issue for COTS</li> </ul>	Yes	No
re-use at 4.9 GHz		




#### Mission Critical Broadband Services for 4.9GHz


- Several broadband (1.5 54Mbps) operational scenarios being targeted
  - Low power PAN (around the person)
  - Medium power WVAN (around the vehicle)
  - Medium to high Power WLAN (around building or incident scene)
  - Fixed and rapidly deployable wireless backhaul links
- Support for mission critical data, video and voice interoperability services with all scenarios



Wireless Vehicular Area Networks
& Personal Area Networks



Wireless Local Area Networks including Outdoor Hotspots




Wireless Backhaul Fixed & Rapidly Deployable




# Interference Rules Need to Account for Channel/Use Flexibility

Adjacent channels with multiple channel bandwidths and power levels


 Multi-service/ Multi-agency (Fully Shared Networks)



 Multi-service/ Multi-agency (Partial Sharing)



 Basic Services (Shared Networks)






### Impact of Mask on Interference




#### **DSRC Mask A vs Mask C**

Difference between center of mask and skirts of DSRC Mask C is at least 10 dB greater than difference of DSRC Mask A (50 dBr vs 40 dBr), which means adjacent channel rejection is also at least 10 dB greater, since shape of skirts is similar.








Near/Far Adjacent Channel Interference when using Mask A versus Mask C: What is minimum separation distance between VM1 and VM2? What is effect on maximum distance PCD can be from VM1?

### 4.9 GHz Adjacent Channel Interference




Mask C provides about 10 dB more protection than Mask A into the adjacent channel (37 dB vs 27 dB adjacent channel suppression at minimum data rate).

Adjacent channel interference (from VM2) limits the maximum distance between the subscriber device (PCD) and the device it is communicating with (VM1).


For the same operational range of the subscriber device, the radius of interference for Mask A is double that of Mask C, i.e., interference area is 4X.



### Simplified Interference Impact Graphically







Estimated Line for FCC mask, adjacent channel suppression = 42 dB.


Interference zone radius = 1.54 m @ 0 dBm, 3.3 m @ 10 dBm, 7.1 m @ 20 dBm



### Mask Impact on Interference Zone


		Interference Radius (meters)		
EIRP	Operating Range	FCC 4.9 Mask	DSRC Mask C	DSRC Mask A
0 dBm	19.3	1.5	2.2	4.6
10 dBm	41.7	3.3	4.6	10
20 dBm	89.9	7.1	10.5	21







## Motorola Will Leverage COTS Technology for 4.9 GHz



**PS - Public Safety Licensed Spectrum** 

**UNII - Unlicensed Broadband Spectrum** 

**DSRC - Digital Short Range Communications Spectrum** 




### **COTS Chipsets Can Be Utilized**


- Motorola issued RFP to seven COTS 802.11a chipset vendors for compatibility with 4.9GHz rules
- Responses indicated that 4 out of 7 vendors could support tightened mask with existing chipsets
  - Software only changes in some cases
  - Software changes and external filters added in other cases



## Measured 4.9 GHz signal using COTS based platform meets FCC mask

To validate the feasibility of using COTS chipsets and meet the FCC and DSRC-C spectral mask, Motorola tested COTS chipsets with an additional external filter.





20 MHz BW

10 MHz BW



# Can Japan 4.9 Products Be Used in U.S. Without Modifications? No


### 4.9 GHz in Japan\*

- Frequency band different than in U.S.
  - 4.9-5.0 GHz & 5.030-5.091 GHz vs. 4.94-4.99 GHz
  - No 10 MHz or 5 MHz channels above 4.95 GHz in Japan
  - Different Channel centers
- 5,10 & 20 MHz bandwidths allowed, but IEEE 802.11j
   does not include 5 MHz option
- Maximum EIRP levels allowed 19 dB below U.S.
- MW Incumbents in 4.9-5.0 GHz can stay until 2007, delaying volume deployment


\* Article 49-21 of Radio Equipment Ordinance



### 4.9 GHz Band Plan Comparison



### **Limited Band Plan Commonality**



### **Conclusions**

- Public Safety users would benefit by minimizing adjacent channel interference at the outset
  - Greater capacity
  - Higher Quality
  - More Spectrally Efficient
- Manufacturers can meet FCC mask or DSRC-C mask by adding inexpensive filter <u>external</u> to COTS chipsets and/or by software changes
- Manufacturers building Japanese 4.9 band or U.S. UNII products must modify equipment to serve U.S. Public Safety 4.9 market, regardless of FCC mask decision
- FCC should be proactive and minimize interference up front before the band is populated

